



*Digital monocular microscope, 400x, integrated 3 MP camera, rechargeable, N-PLAN objectives*

<b>Observation Method - Transmitted Light</b>	Brightfield	Yes
	Simple polarized light	As optional
<b>Main Body</b>	Type	Upright
	Construction material	Aluminum die-cast
<b>Head</b>	Type	Monocular
	Inclination	30°
	360° rotating	Yes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
<b>Eyepieces</b>	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
	High eyepoint (for glass wearers)	Yes
<b>Nosepiece</b>	Positions	Quadruple
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
<b>Objectives</b>	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-400x
	Type	N-PLAN
		4x/0.10, W.D. 15.2 mm
		10x/0.25, W.D. 5.5 mm
	40x/0.65, W.D. 0.45 mm	
<b>Stage</b>	Type	Double layer
	Dimensions (mm)	125x116
	Moving mechanism	Rack and pinion
	Moving range (mm)	70x30
	Material	Anti-scratch painting

	Specimen holder	Yes
	Slide number	1
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
<b>Condenser - Single Position</b>	Type	Abbe
	Numerical aperture (N.A.)	1.25
	Diaphragm	Iris
	Centrable	Pre-centered
	Focusable	By rotation
<b>Focusing System</b>	Type	Coaxial coarse & fine
	Coarse total travel (mm)	16
	Fine total travel (per single rotation) (mm)	0,4
	Fine graduations	100
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
<b>Transmitted Illumination</b>	Type	X-LED
	X-LED type	X-LED1
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1,5
<b>Power Supply for Transmitted Illumination</b>	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Rechargeable batteries	Yes
	Battery type	Li-ion (battery pack)
	Working time of batteries (hours)	15
Charging time of batteries (hours)	6	
<b>Accessories Included</b>	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
	USB cable (m)	1,8
<b>Additional Information</b>		Mirror for transmitted light (as optional)
<b>Product Dimensions</b>	Height (mm)	365
	Width (mm)	170
	Depth (mm)	320

<b>Product Weight</b>	(kg)	4
<b>Camera General specifications</b>	USB output	Yes
	C-Mount	Yes
	Dimensions (mm)	Included in the microscope head
	Weight (kg)	Included in the microscope head
<b>Sensor</b>	Camera resolution (n° of pixels: W x H)	2048x1536
	Color / Monochrome	Color
	Sensor Size	1/2.5"
	Sensor Technology	CMOS
	Sensor Type	APTINA CMOS
	Image Format	4/3
	Pixel Size (mm)	2.8x2.8
	Acquisition technology	Rolling shutter
	Sensitivity	0.53 V/lux-second
	Signal/Noise Ratio (DB)	40.5
	Dynamic range (DB)	66.5
	ADC conversion	12 Bit
	Color Depth	8 Bit
	Exposure time	0.1 - 1.5 sec
	Binning	1x1
IR filter	Yes	
IR filter range (nm)	380-650 (IR CUT)	
<b>USB</b>	Camera resolution (MP)	3.1
	USB standard	USB2.0
	Frame rate full resolution (fps)	4@2048x1536
	Frame rate other resolution (fps)	8@1280x1024; 30@640x480
<b>Camera Power Supply</b>	Output voltage	PC USB
	LED indicator	Yes
<b>Environment</b>	Working Temperature	-10°C up to +50°C
	Storage Temperature	-20°C up to +60°C
	Relative Humidity	30% to 80%
	Storage Humidity	10% to 60%
<b>Operating System</b>	OS	Windows 8
	OS	Windows 10 (32Bit)
	OS	Windows 10 (64Bit)
	OS	Windows 11
<b>Available Software</b>	PC SW	PROVIEW
<b>PC requirements</b>	PC	CPU: Intel Core2 - 2.8GHz or higher
	PC	RAM: 2GB or more
	PC	USB 2.0