v 1.0 2019



Gemological binocular stereozoom microscope, 7x...45x, pillar stand, transmitted & incident light

Observation Method -	District	V
Transmitted Light	Brightfield	Yes
	Darkfield	Yes
	Simple polarized light	As optional
Observation Method -	Drichtfield	Voc
Incident Light	Brightfield	Yes
	Darkfield	Yes
	Simple polarized light	As optional
Head	Tura	Binocular
пеац	Type Construction material	
		Plastic mold / Aluminum gears
	Inclination	45°
	360° rotating	Yes
	Interpupillary distance (mm)	51-75
	Dioptric adjustment	On both tubes
	Fixing screw for eyepieces	Yes
	Head holder internal diameter (mm)	76
	Tube inner diameter (mm)	30
Evenieses	Field number (mm)	21
Eyepieces	` '	10x
	Magnification Micrometric scale	
		As optional
	Diameter of micrometer glass (mm)  High eyepoint (for glass wearers)	Yes
		Yes
	Rubber cup	res
Objective	Optical system	Greenough
	Anti-fungus treatment	Yes
	Objective Type	No
	Zoom type	Parfocal achromatic
	Working distance (mm)	100
	Standard magnifications	7x-45x
	Zoom ratio	6.43
Focusing System	Туре	Coarse
	Coarse total travel (mm)	50
	Adjustable tension	Yes
	Head holder internal diameter (mm)	76
	\ /	
Stand	Туре	Pillar
	Pillar diameter (mm)	32
	i mai diameter (mm)	J.L
01		
Stage	Gemological clamp	Yes, adjustable

Transmitted	Туре	LED
Illumination	Darkfield illuminator	Yes, side-emitting LEDs
	Lever for dark background insertion	Yes
	20vor for dank background incordor.	Yes, 3 modes:
	Calastar for illumination made	- brightfield only
	Selector for illumination modes	- darkfield only
		- both brightfield and darkfield.
	Light source power (W)	2
	Illuminance (lux)	6,000
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	3
Incident Illumination	Туре	Halogen
	Light source power (W)	15
	Illuminance (lux)	35,000
	Brightness control	Manual
	Lifetime (hours)	> 3,000
	Temperature (K)	3,500
	Max. required power (W)	19
Power Supply for Illumination	Туре	Internal
	Microscope connector	C13 plug
	Power plug type	Schuko
	Input voltage	110/240 Vac, 50/60 Hz
	Output voltage	12 Vdc
Accessories Included	Dust cover	Yes
	User Manual	Digital version (downloadable)
<b>Additional Information</b>	Maximum sample height (mm):	150
	maximam campio neight (min).	100
Designation of Discounting		0.45
Product Dimensions	Total height (mm)	315
	Head height (mm)	230
	Head width (mm)	175
	Head depth (mm)	175
	Base height (mm)	60
	Base width (mm)	200
	Base depth (mm)	260
Product Weight	(kg)	5.5